

LS151 Primer Resurfacing Primer

PHYSICAL DESCRIPTION / PROPERTIES

Appearance	Blue viscous paste
Compressive Strength	-
Flexural Strength	-
Bond Strength	0.8MPa (to glazed tiles)
Setting Times	60 minutes
Working Time	-
Adjustability Time	-
Application Temperatures	5 °C and 30 °C (surface temperature)
Classification	-

COVERAGE

10mm Roller	Area m2 per 15L pail
1 coat	Up to 180 m ²
2 coats	Up to 100 m ²

PREPARATION / APPLICATION

Surface Preparation	All substrates must be clean and free from any contaminates. Substrates should also be fastened and well secured. Cureflex LS151 Primer may be applied using brush or roller
Priming	None
Mixing	Generally does not need mixing. If however product has been stored/unused for prolong period, only then product may require stirring. Do not dilute Cureflex LS151 Primer
Curing	Product dries after 1 hour at 18 °C with 50% relative humidity
Application	Apply 1 x coat at minimum coverage of 1L per 12 m ²
Precautions	None
Substrates	Stainless steel , brass, copper and most metals, ceramic tiles, glass, porcelain tiles, PVC, vinyl, Laminex, existing painted surfaces
Clean Up	In water while wet, once product dries it needs to be removed by solvent or mechanical means

LS151 Primer Resurfacing Primer

HEALTH HAZARD INFORMATION

Health Effects

Chronic	Principal routes of exposure are by accidental skin and eye contact and by inhalation of vapours especially at higher temperatures. Contact with unprotected bare skin; inhalation of vapour, mist or dust in work place atmosphere; or ingestion in any form, should be avoided.
Swallowed	No data supplied but polymer is not expected to be harmful.
Eye	May be an eye irritant.
Skin	Prolonged or repeated contact with skin may result in slight skin irritation.
Inhaled	Excessive exposure to vapours may cause slight irritation to eyes, nose and throat.

FIRST AID

Swallowed	Drink plenty of water. Seek medical assistance. Decision on induction of vomiting to be made by qualified person.
Eye	Immediately flush with large amounts of water for at 5-10 minutes; lifting upper and lower lids. Seek medical attention if irritation persists.
Skin	Wash with water and soap. Seek medical attention if irritation persists
Inhaled	If affected, move subject to fresh air. Seek medical assistance if symptoms persist.
First Aid Facilities	Ensure availability of eye wash fountains and/or water access.
Advice to Doctor	Treat symptomatically.

PRECAUTIONS FOR USE

Personal Protection

Respirator Type (AS/NZS 1716)	Where concentrations in air may exceed the recommended exposure limits, or work practice or other means of exposure reduction are not adequate, approved respirator may be necessary to prevent overexposure by inhalation.
Glove Type	Neoprene/rubber gloves.
Eye Protection	Safety glasses as appropriate.
Clothing	Protective clothing to cover body parts, e.g. long sleeved overalls or similar; and boots.
Other	Wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.
Flammability Fire Hazards	Product is non flammable according to the Australian Code for the Transport of Dangerous Goods. However, dried film will burn in a general fire.

Demtech Australia Pty Ltd
P.O. Box 4535 Knox City
Centre VIC 3152

