



# HV124 Silane Construction Adhesive

The information contained within this Technical Data, details product description, health and safety hazard information of the product and how to safely handle and use the product in the workplace. Also refer to MSDS for more information. Each user of this product should read the MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact Demtech Australia Pty Ltd. Demtech Australia Pty Ltd makes no representation as to the completeness and accuracy of the data contained in this data sheet. It is the user's obligation to evaluate and use this product safely, and to comply with all relevant Federal, State and Local Government laws and regulations. Demtech Australia Pty Ltd shall not be responsible for loss, damage or injury resulting from reliance upon or failure to adhere to any recommendation or information contained herein, from abnormal use of the material, or any hazard inherent in the nature of the material.

### STATEMENT OF HAZARDOUS NATURE

Not classified as hazardous according to criteria of Worksafe Australia.

### IDENTIFICATION

Product Name	HV124 Silane construction adhesive
Other Names	None assigned
UN Number	None assigned
Dangerous Goods Class	None assigned
Subsidiary Risk	None assigned
Shipping Name	None assigned
Hazchem Code	None assigned
Poisons Schedule Number	None assigned

### DESCRIPTION

Cureflex HV-124 (High Viscosity) silane adhesive is a premium grade, solvent free adhesive designed for bonding porous and non porous products and materials on vertical or horizontal substrates. This high performing adhesive is specifically engineered to provide instant 'grab' adhesion between product surfaces and substrates offering exceptional fast curing properties without shrinkage, odours or vapours.

### MAIN USES

For high performance bonding applications over a range of substrates including timber, fibrous sheeting, con-crete, acoustic underlay, plastics, rubber cork, vinyl, laminex, paints, ceramics, polystyrene and an array of non porous and porous surfaces



Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152



# HV124 Silane Construction Adhesive

## PHYSICAL DESCRIPTION / PROPERTIES

Appearance	Viscous paste
Bond Strength	Tear strength - 3.0 N/mm <sup>2</sup> Shear strength - >2.0N/mm <sup>2</sup>
Setting Times	Tack Free - 30 mins at 23 °C and 50% RH, Curing - 2.5mm/24hrs at 23 °C and 50% RH
Application Temperatures	+5 °C to 35 °C
Classification	None

## COVERAGE

Thickness – Notched Trowel Size	Area m <sup>2</sup> per 15kg pail
3mm V	
4m Standard	
6m Standard	

**NOTES:**

As a structural adhesive for panel bonding allow 1kg per 1m<sup>2</sup> coverage

Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152

www.demtech.com.au  
info@demtech.com.au  
Technical Support: 1300 300 090



# HV124 Silane Construction Adhesive

## PREPARATION / APPLICATION

**Surface Preparation** Surfaces must free of contaminants or foreign material. Ensure substrate is sound and free of any loose or unsecured areas prior to application

**Priming** Priming on building substrates is not required once surfaces have been appropriately prepared and cleaned

**Mixing** No mixing required

**Curing** Curing - 2.5mm/24hrs at 23 °C and 50% RH

**Application** A minimum 2mm dried adhesive bed is required to achieve maximum elastic bonding properties  
If adhering two non-porous surfaces together, ensure 1-2cm gaps between bead lines are allowed to allow air flow for curing.

**Precautions**

- This adhesive is not designed for use in permanently immersed areas.
- Not suitable for continuous immersion in solvents or industrial grade chemical solutions.
- For over coating this product, check with Demtech for compatible coatings.
- Do not apply when surface temperature is below 5 °C or above 35 °C.
- Avoid applying in hot conditions as warm temperatures may cause sealant to skin.

**Substrates** Surfaces must free of contaminants or foreign material. Ensure substrate is sound and free of any loose or unsecured areas prior to application

**Clean Up**

- On hands or skin while product is wet – use soap and water. Once cured use solvent free hand cleaners.
- On surfaces, uncured material can be removed using methylated spirits/denatured alcohol.
- Areas where product has dried will need to be removed using industrial strength solvent such as Acetone or Xylol.

Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152

www.demtech.com.au  
info@demtech.com.au  
Technical Support: 1300 300 090

# HV124 Silane

## Construction Adhesive

### HEALTH HAZARD INFORMATION

#### Health Effects

Chronic	Skin sensitivity can be developed following prolonged and repeated contact
Swallowed	Toxicity caused by single oral dosage is low
Eye	May cause sensitisation
Skin	May cause skin sensitisation
Inhaled	Product is odourless.

### FIRST AID

Swallowed	In case of ingestion irritation, seek medical attention.
Eye	Rinse carefully with plenty of clean water and seek medical attention.
Skin	Contact with skin, remove excess by hand and wash effected area with plenty of soapy water.
Inhaled	In case of breathing irritation, seek medical attention.
First Aid Facilities	Ensure availability of eye wash fountains and/or water access.
Advice to Doctor	Treat symptomatically. If poisoning occurs, contact a doctor or Poisons Information Centre.

### PRECAUTIONS FOR USE

#### Personal Protection

Respirator Type (AS/NZS 1716)	Where concentrations in air may exceed the recommended exposure limits, work practice or other means of exposure reduction are not adequate, approved respirator may be necessary to prevent overexposure by inhalation.
Glove Type	Neoprene/rubber gloves.
Eye Protection	Safety glasses as appropriate.
Clothing	Protective clothing to cover body parts, e.g. long sleeved overalls or similar; and boots.
Other	Wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.
Flammability Fire Hazards	No unusual fire danger. The flash point is >610C. Not spontaneously combustible

# HV124 Silane Construction Adhesive

## SPILLS & DISPOSALS

Clean Up Spills	Do not dispose of in drains. Clean up spills by covering with absorbent material (saw dust, sand etc). After 1 hour collect in a waste container. Do not close container (carbon dioxide is developed). Keep humid and leave for several days in open air in a controlled area. Further disposal by incineration in accordance with local laws in force.
Disposal	Dispose of in accordance with local, state and federal regulations.
Precautions for Clean Up Crew	Neoprene rubber gloves

## FIRE / EXPLOSION HAZARDS

Hazard of Use / Storage	Not spontaneously combustible
List of Dangerous Decomposition or Combustion Products	In event of fire the following substances may form: carbon monoxide and nitric acid
Types of Extinguisher	Foam, CO2 and dry chemical. Use water spray to cool fire exposed surfaces and protect personnel.
Precautions	<ul style="list-style-type: none"> <li>- This adhesive is not designed for use in permanently immersed areas.</li> <li>- Not suitable for continuous immersion in solvents or industrial grade chemical solutions.</li> <li>- For coating this product, check with Demtech for compatible coatings.</li> <li>- Do not apply when surface temperature is below 5 °C or above 35 °C.</li> <li>- Avoid applying in hot conditions as warm temperatures may cause sealant to skin.</li> </ul>
Protective Clothing	Appropriate fire fighting clothing
Reactivity	None

## OTHER INFORMATION

Ecology	Avoid contaminating waterways and sewers. This product is not biodegradable.
Packaging & Labelling	Product remains stable when handled to recommended storage conditions
Precautions for Use	Avoid excessive heat
Reactivity Data	Methoxysilane base products react with water producing methanol. The products are insoluble in water and as they are denser than water, precipitate to the bottom, slowly reacting on the interface.



# HV124 Silane Construction Adhesive

## CONTACT POINT

Technical Department

Demtech Australia Pty Ltd (ABN : 91 131 136 706)

16 Logis Blvd, Dandenong South 3175

P: 1300 300 090

Email: [info@demtech.com.au](mailto:info@demtech.com.au)

Australia Poisons Information Centre

13 11 26

Police & Fire Brigade

000

General

The information contained herein is based on present state of our knowledge and does not guarantee certain properties. Recipients of our products must take responsibility for observing laws and regulations. The information contained within is published free of charge in good faith and is based on technical data that Demtech Australia Pty Ltd considers to be reliable.

Disclaimer

The information within is intended for use by skilled and/or persons with technical knowledge. They are required to make their own assessment and use the product at their own risk and discretion. Information contained in this product sheet conforms to the standard detail recommendations and specification for the use of Demtech Australia products as of the date of this document. Demtech Australia Pty Ltd make no other warranties and assumes no liability, expressed or implied.

To ensure that you are using the most complete and up to date information, contact Demtech Australia Pty Ltd.

Demtech Australia Pty Ltd  
P.O. Box 4535 Knox City  
Centre VIC 3152

[www.demtech.com.au](http://www.demtech.com.au)  
[info@demtech.com.au](mailto:info@demtech.com.au)  
Technical Support: 1300 300 090